Product Summary LARA-R3121 module

LTE Cat 1 module based on the u-blox LTE chipset with a built-in GPS receiver

Connectivity, positioning, and timing solution: all in one module

- Supports 3GPP Rel. 12 Power Saving Mode for long battery life
- Provides position data and timing, indoors and outdoors
- · Features end-to-end trusted domain security
- Provides signal optimization and congestion control
- Enables easy migration from other u-blox module form factors and technologies





Automotive

24.0 × 26.0 × 2.6 mm

Product description

The LARA-R3121 LTE Cat 1 module is a pioneer, as the only module designed from the ground up for IoT applications. At its core is the UBX-R3 chipset, u-blox's own cellular modem with silicon-integrated GPS receiver.

The UBX-R3 platform provides a wide range of features for secure and robust operation, such as secure boot¹, transport layer security, embedded FOTA client for secure software updates over the air, jamming and spoofing¹ detection, and an integrated security agent for monitoring and detecting security threats¹.

Based on u-blox's innovative software-defined modem engine, LARA-R3121 offers advanced 3GPP features, such as Rel. 12 Power Saving Mode for long battery life, Extended Access Barring (EAB) feature for signaling optimization/ congestion control, and QoS enhancement for mission critical applications.

Thanks to the integration of a u-blox 8 GPS receiver directly in the UBX-R3 chipset, LARA-R3 cost-effectively provides highly reliable and accurate positioning data both indoors and outdoors. In addition, LARA-R3121 offers practical hybrid positioning, in which GPS position is enhanced with u-blox

1 = Available in future FW version

CellLocate[®] location data. Uniquely, it also provides a robust and accurate timing reference, CellTime[™], which is obtained from available GPS or LTE base stations, allowing simple and cost efficient implementation of timing solutions.

The LARA-R3121 comes in a compact LGA package with several interfaces and a fully embedded IP stack, making it easy to integrate in size-restricted designs and suitable for a wide range of medium data rate applications.

LARA-R3121 modules are perfectly suited for use in industrial IoT applications, including asset/vehicle tracking, smart meter gateways, mobile digital signage, connected health applications, and low latency applications such as point-of-sale systems. Its data rate enables bi-directional video streaming, as necessary for security and video surveillance.

The LARA form factor enables straightforward migration from u-blox SARA (2G and 3G) and TOBY (LTE) modules, maximizing reuse of previous hardware investments. And USB drivers and RIL software for Linux, Android and Microsoft are available free of charge, optimizing time-to-market and product cost.

Model	Region	Acc	ess	Technolo	рgy	GN	ss			Inte	erfac	es				Fea	ture	s									Gra	de	
		3GPP Release Baseline	LTE FDD category	LTE bands	Rx diversity	GPS / QZSS receiver	GNSS via Modem	AssistNow software	CellLocate®	UART	USB 2.0	HSIC *	SDIO * (Master/Slave)	DDC (I ² C)	GPIO	Antenna supervisor	Jamming detection	CellTime™	Secure boot	Security agent	Embedded TCP/UDP	Embedded HTTPS, FTPS	LWM2M client	FOTA client	Time pulse (via GPIO)	Dual stack IPv4 / IPv6	Standard	Professional	Automotive
LARA-R3121	Europe	10	1	3, 7, 20	٠	•	٠	•	•	1	1	1	1	1	10	•	٠	•			•	٠		•	٠	•		•	

Product selector





LARA-R3121 module



Features	
LTE	Cat 1 (10 Mbit/s DL, 5 Mbit/s UL) 3GPP Release 10 Plus MTC features from Releases 11 and 12: Power Saving Mode, Release 12 Extended Access Barring (EAB) - Enhancements QoS Enhancements for low latency and mission critical applications
FDD bands	LARA-R3121: Bands 3, 7, 20 (Europe) All channel bandwidths: 1.4 – 20 MHz Rx diversity Public Warning System (PWS) 1
SMS	MT/MO PDU/Text mode
Network	Status Indication via LED
Protocols	Dual stack IPv4 / IPv6 Embedded TCP/IP, UDP/IP HTTP/FTP, HTTPS/FTPS
Security / Robustness	Security agent ¹ , secure boot ¹ , transport layer security (TLS1.2), secure debug interface, FOTA client, jamming and spoofing ¹ detection
Device Management	LWM2M client ¹

Positioning features

GNSS receiver	72-channel u-blox 8 engine GPS/QZSS L1 C/A
Assistance GNSS	AssistNow Online AssistNow Offline OMA SUPL & 3GPP compliant 1
Acquisition	Cold: 30 s / Aided: 3 s / Reacquisition: 1 s
Max nav. update rate	Up to 10 Hz
CellLocate®	Cell tower location data to supplement positioning receiver data

Interfaces

Serial	1 UART 1 USB 2.0 (high-speed, 480 Mbit/s) 1 HSIC ¹ 1 SDIO ¹ 1 DDC (I ² C) Time pulse (via GPIO)
GPIO	Up to 10 configurable GPIOs
USIM	Supports 1.8 V and 3.0 V, SIM toolkit

1 = Available in future FW version

Package

100 nin I GA	(1 and Grid Array): 26.0 x 24.0 x 2.6 mm < 4 d	

Electrical data

Power supply	3.3 V to 4.4 V	
Power consumption	TBD	

Environmental data, quality & reliability

Operating temperature –40 °C to +85 °C (extended range)	
RoHS compliant (lead-free)	
REACH compliant	
Manufactured in ISO/TS 16949 certified production sites	

Certifications and approvals

LARA-R3121	GCF, RED (formerly known as R&TTE), and
	operator approvals

Support products

EVK-R3121	Evaluation kit for LARA-R3121
RIL software	Available for Android
USB driver	Available for Windows 10 (standard and loT), Windows 7, 8

Product variants

LARA-R3121 LTE Cat 1, Bands 3, 7, 20 (Europe)	
---	--

Further information

For contact information, see www.u-blox.com/contact-us.

For more product details and ordering information, see the product data sheet.

Legal Notice:

u-blox reserves all rights to this document and the information contained herein. Products, names, logos and designs described herein may in whole or in part be subject to intellectual property rights. Reproduction, use, modification or disclosure to third parties of this document or any part thereof without the express permission of u-blox is strictly prohibited.

The information contained herein is provided "as is". No warranty of any kind, either express or implied, is made in relation to the accuracy, reliability, fitness for a particular purpose or content of this document. This document may be revised by u-blox at any time. For most recent documents, please visit www.u-blox.com. Copyright © 2018, u-blox AG